## CLAIMS

production of nonwoven surfaces intended to be used as interlining or filling fabric for garments, characterized in that the fibers have three-dimensional crimps and a yarn count of between 0.9 dtex and 5 dtex, preferably between 1 and 3.3 dtex.

- The use as claimed in claim 1,
   characterized in that the fibers are obtained by spinning a polyamide-based composition.
  - 3. The use as claimed in claim 1 or 2, characterized in that the polyamide is chosen from the group comprising nylon-6,6, nylon-6, nylon-6,10, nylon-4,6, nylon-11, nylon-12 and copolyamides thereof.
  - 4. The use as claimed in one of the preceding claims, characterized in that the fibers are crimped in a pneumatic crimping process by packing a tow into a nozzle.
- 5. The use as claimed in claim 4, characterized in that the gas phase used in the pneumatic crimping process is chosen from the group comprising air, steam or an air/steam mixture.
- 6. The use as claimed in one of the
  preceding claims, characterized in that the fibers have
  prograil-shaped loops and/or curls.

fabric for garments, comprising at least fibers with a three-dimensional crimp.

Zust ars

- 8. The nonwoven as claimed in claim 1, characterized in that it is used as interlining in the making-up of garments.
- 9. The nonwoven as claimed in claim 7 or 8, characterized in that it includes at least one layer formed from a nonwoven comprising fibers with a three-
  - 10. The nonwoven as claimed in one of claims 7 to 9, characterized in that it forms a napped textile surface.
- 11. The nonwoven as claimed in one of claims 15 7 to 10, characterized in that it has a grammage of between 10  $g/m^2$  and 200  $g/m^2$ , preferably between 20 and 100  $g/m^2$ .

adda Aby b 3